

CORNER TIES: (HORIZONTAL DISTANCES)

NW COR. SW1/4 SEC. 18-T20N-R6E
FOUND A SURVEY MARKER FLUSH WITH ASPHALT SURFACE.
NE 46.44' TO A 5/8" IRON BAR
SE 54.50' TO THE TOP NUT OF A FIRE HYDRANT
SE 68.18' TO A PUNCH MARK IN THE NORTH SIDE OF A LIGHT POLE
SW 71.55' TO THE NW CORNER OF A TRANSFORMER PAD
SW 46.94' TO A CHISLED "X" IN A CONCRETE WALK BY THE CURB
NW 38.68' TO A PUNCH MARK IN THE NORTHEAST BOLT OF A LIGHT POLE BASE

NE COR. NW1/4 SW1/4 SEC. 18-T20N-R6E
FOUND A MAG NAIL AND WASHER FLUSH WITH ASPHALT SURFACE.
NNE 66.83' TO THE SW CORNER OF A CONCRETE BLOCK PORCH
ENE 46.53' TO A PUNCH MARK IN THE SOUTH SIDE OF A MANHOLE RIM
SE 51.39' TO A CHISLED "X" IN A CONCRETE HEADWALL
SSW 53.57' TO THE NE CORNER OF A BRICK PORCH COLUMN

NE COR. SW1/4 SEC. 18-T20N-R6E
FOUND A CHISLED "X" AND STAR DRILL HOLE IN THE CONCRETE SURFACE.
SE 62.73' TO THE SW CORNER OF A TELEPHONE RISER PEDESTAL
S 100.00' TO A 5/8" REBAR
S 200.00' TO A 5/8" REBAR (2 REBARS ON LINE WITH SOUTH QUARTER CORNER OF SECTION 18-T20N-R6E)
S 43.75' TO A REBAR IN THE CENTER OF A CONCRETE R.O.W. MARKER
WNW 82.95' TO A "U" POST AT THE BASE OF A TRANSFORMER ON THE EAST SIDE
NNW 73.95' TO THE TOP NUT OF A FIRE HYDRANT

CLIENT NAME:	OLSON / PEARSON AUCTION & REALTY
PROJECT NUMBER:	SU - 1432
DATE:	MARCH 17, 2007
FIELD BOOK:	DODGE COUNTY #8
SCALE:	1" = 100'
REVISION DATE:	
SHEET:	2 OF 2

LEGEND

	MONUMENT FOUND	(5/8" REBARS, UNLESS NOTED OTHERWISE)
	MONUMENT SET	(3/8" X 24" REBARS, WITH A PLASTIC CAP L3, 517" UNLESS NOTED OTHERWISE)
	TEMPORARY POINT	
C.T.P.	CRIMPED TOP PIPE	
O.T.P.	OPEN TOP PIPE	
C	COMPUTED DISTANCE	
D	DEEDED DISTANCE	
M	MEASURED DISTANCE	
P	PLATTED DISTANCE	
R	RECORDED DISTANCE	

NOTE: ALL BEARINGS ARE ASSUMED

GLS SURVEYING
INC.

1618 SHAMROCK BLVD.
YUTAN, NE 68073
OFFICE: (402) 625-2692
CELL: (402) 618-9133